
Lumen Logic™ LogiPath G2 Path Light



| Project Name: | | |
|--|------|--|
| Date: | | |
| Location: | | |
| Туре: | | |
| Model Number: | | |
| Quantity: | | |
| Quantity: Prepared By: Comments: | | |
| Comments: | | |



Dimensions



LumenLogic[™]

15486 N. Nebraska Ave. Lutz, FL 33549 (833) 695-8636

Notes

 Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions.
Incandescent Equivalent: The incandescent equivalent as presented is an approximate number and is for reference only.

Description

Specifications

The Lumen Logic[™] LogiPath G2 Path Light is a professional-grade low-voltage (12V) light. Constructed of durable, high-quality brass with an antique bronze finish. Includes a 3W LED GU4 Bi-Pin bulb and mounting stake. Ideal for illumination on walkways, driveways, garden beds, and patios. Backed by a lifetime warranty.

Materials

| matorialo | |
|--------------|----------------------------|
| Construction | Cast Brass |
| Finish | Bronze |
| Lead Wire | 25' 18AWG, SPT-1 |
| Lens | Convex Clear Polycarbonate |
| Mounting | 9" PVC Stake |
| | |

Photometrics

| Light Source | LED GU4 Bi-Pin |
|-----------------------------|----------------|
| Light Output (Lumens) | 100 Lumens |
| Beam Angle | 12' Diameter |
| Color Temperature (CCT) | 2700K |
| Color Rendering Index (CRI) | >80 |
| Lamp Life (L70) | 30,000 Hours |

Electrical

| Energy Consumption (watts) | 3.0 Watts |
|----------------------------|-------------------------|
| Power Factor | 0.66 |
| Operating Voltage Range | 12-15 Volts |
| Power Supply | Low Voltage Transformer |

Installation

Orientation

Directed Downwards only

Certifications

| Certifications | UL & cUL listed |
|----------------|-----------------|
| Warranty | Lifetime |

***:** LumenLogic[™]